



VERSA-DRILL VERSA-SONIC

AIR ROTARY, WATER WELL, GEOTHERMAL, EXPLORATION, CATHODIC PROTECTION



VERSA-DRILL VERSA-SONIC

20,000 LBS PULLBACK

STANDARD FEATURES AND SPECIFICATIONS

CARRIER

Peterbilt 548 6x4
PACCAR PX-9 with 350 HP
Allison Transmission automatic

TRANSFER CASE

Marmon-Herrington
Safe Shift control system

HYDRAULIC SYSTEM

Bosch Rexroth
3 auxiliary hydraulic connections

TOP HEAD

Sonicor 50K

DERRICK & FEED SYSTEM

26' top head stroke
25,000 lbs pullback
22,100 lbs pulldown

MAIN WINCH

12,000 lb.

CENTRALIZER TABLE

Hydraulic breakout system
13.5" through

CONTROL PANEL

Electric over hydraulic controls
Marine grade electric switches
Hydraulic joysticks
4" touch screen display
Twin height adjustable aluminum platforms
Aluminum console cover

LEVELING JACKS

Four 36" stroke independently controlled with precision digital inclinometer leveling

NIGHT LIGHTS

4 LED night lights

TOOL BOXES

59"x24"x26"
24"x24"x26"
12"x12"x32"

OVERALL DIMENSIONS

Length: 35'10"
Width: 8'
Derrick up height: 40'
Derrick down height: 13'2"

OPTIONS (at additional cost)

MAIN WINCH

18,000 lb.

AUXILIARY WINCH

4,000 lb.

AIR COMPRESSOR

45 cfm/150 psi Vanair
500 cfm/200 psi Vanair

WATER INJECTION

75 gpm American Mfg Company

ADDITIONAL OPTIONS

n-deck grouter (multiple options)
Hose reel (multiple options)
Aluminum catwalk
Remote pendant for winches & jib boom
Versa-Rod spinner